

MONOFLEX NANO HYBRID

Long lasting, new generation waterproofing roof coating.

Description

One component hybrid, water-based roof waterproofing membrane, ready to use which creates after curing, a protective film impervious to moisture with excellent elasticity and resistance to extreme weather conditions and stagnant water.

Examples of applications

MONOFLEX NANO HYBRID is used for waterproofing on surfaces of cement, concrete, wood, metal, tiles, bitumen membranes on horizontal and vertical surfaces such as:

- Terraces
- Balconies
- Flooring
- Drainage channels
- Buildings made of bricks or concrete blocks
- Roofing substrates etc.

Characteristics - advantages

- Covers wide range cracks, providing absolute protection from moisture (> 2mm)
- Cures with sunlight and has no stickiness even at very high temperatures.
- Reflects sunlight energy significantly reducing the temperature of the outer surface (> 85%) which results in a reduction in energy consumption during the summer months.
- Prevents deposits of dust and dirt pickup keeping its high whiteness.
- Excellent adhesion with substrates such as: ceramic tiles, mortars, zinc, aluminium, brick, wood, concrete, bitumen etc.
- Long lasting life (10 years).
- Extremely economical and easy to use.
- Capable patency

Specifications

Form: White paste

Density: 1,3 kg / L

Application temperature and substrate temperature: + 5 °C to + 35 °C

Elongation at break (ASTM D 412): >300%

Tensile strength EN 1542: > 1,5 N / mm²

TDS BAUER- MONOFLEX NANO HYBRID -EN- 10.06.2019

Drying time to touch: 2 hours at 20 °C

Full drying time: 10-12 hours at 20 °C

Capillary water absorption: <0.01 kg / m² • h^{0.5}

Substrate preparation

Ensure stable surfaces. Remove loose, detached parts, dirt, grease, dust, etc. Fill and repair any major gaps and cracks with suitable repairing products of BAUER. The material can be applied regardless the moisture percentage of the substrate.

Instructions for use

MONOFLEX NANO HYBRID is ready to use. It requires only stirring in the container for a short period until the mixture is homogeneous. The material is applied by brush or roller in two hands at least crosswise. Dilute with 10% water for a layer as a primer. The second coat is applied onto the first crosswise when completely dry (when the previous layer is walkable). If needed, apply a third layer, in the same manner. Make sure that the material is filling all the gaps. In cases of large cracks, edges and where improved material properties required, place between the two layers reinforcing mesh (glass fibre or polyester).

In cases requiring local filling cracks, inject in direct MONOFLEX NANO HYBRID (thinned 5% with water) and then reinforce with mesh. The application is not suitable in days with intense sun (temperature greater than 35 °C) or rain and days where temperatures below zero are expected to fall. Immediately after use, clean the application tools with water

Consumption

1-2 kg /m² Consumption of MONOFLEX NANO HYBRID, depends on the porosity and the flatness state of the surface

Packaging

Containers 15 kg

Storage

In shaded, preferably sheltered areas protected from frost, high temperature and sun exposure for at least 12 months.

Notes

Technical details, properties, recommendations and information on BAUER products are supplied in good faith. They are based on the company's research and experience, provided that they are stored and applied under normal conditions. As the method of using materials as well as project and environment conditions are beyond the control of the company in each individual application setting, the product user is held solely responsible for the result of application. No responsibility under any legitimate relationship can be substantiated against the company, based on the information set out hereunder. Product users are advised to refer to the latest revision of the technical manuals available.

Other information

BAUER BUILDING TECHNOLOGIES

Megara Industrial Estate, Attica

Tel: 210 5744222

Fax: 210 5740777

Email: info@netbauer.com

[http// www.netbauer.com](http://www.netbauer.com)

Frankfurt, Reg. No 312310 QM
Qualitätsmanagementsystem
Zertifiziert nach DIN EN ISO 9001

